

CE

EXCEED IN QUALITY AND MORE



300

Electrolyte Analyzer



Genru

CE 300

Electrolyte Analyzer



General Features

Throughput: 60 samples/hour
 Configuration: 6 types
 Principle: ISE(Direct Ion Selective Electrode)
 5.6-inch color touch screen
 Auto sampling, washing, calibration
 Maintenance-free electrodes, 12 months lifespan
 Simple tubing system, easy maintenance
 CE marked

Technical Specifications

Sample type: Serum, Plasma, Urine, etc.
 Sample size: More than 2 sizes
 Sample volume: 100-200 μ L
 Reagent consumption: 2 times sample volume
 Two Calibration Mode: Automatic or On-demand
 Closed reagent, real time monitoring reagent
 Printer: Internal thermal printer
 Multiple language: English, Russian, etc.
 Storage: Up to 50,000 results
 Interface: RS-232, support LIS
 Working temperature: 15-30 $^{\circ}$ C
 Humidity: 20%-80%
 Dimension: 430 \times 275 \times 410mm
 Power: AC100~240V, 50/60 Hz, 80W
 Net weight :8 kg

Reagent

DS-I(NO.3) Standard A Standard B (390/160 mL)
 Cleaning Solution (250 mL)
 PVC Electrode Activating Solution (50 mL)
 DS- Ref Ref. Filling Solution (10 mL)
 DS- ISE Filling Solution (10 mL)
 Deprotein Solution
 (R1: Diluent 18mL/bottle \times 1; R2: Protease powder 100mg/bottle \times 6)



Parameters

K⁺, Na⁺
 K⁺, Na⁺, Cl⁻
 K⁺, Na⁺, Cl⁻, iCa²⁺, TCa, pH
 K⁺, Na⁺, Cl⁻, iCa²⁺
 K⁺, Na⁺, Cl⁻, Li⁺
 K⁺, Na⁺, Cl⁻, iCa²⁺, pH, TCa, TCO₂, AG, KT

Performance

Ion	Linearity (mmol/L)	CV
K ⁺	0.3-20.0	≤ 1.0%
Na ⁺	20.0-200.0	≤ 1.0%
Cl ⁻	20.0-200.0	≤ 1.0%
iCa ²⁺	0.1-6.0	≤ 1.5%
pH	3.0-11.0	≤ 0.5%
Li ⁺	0.2-5.0	≤ 1.5%

All rights reserved. Specifications subject to change without prior notice



Genrui Biotech Inc.

Add: 6F, Shanshui Building B, Nanshan Yungu Innovation Industrial Park, 1183 Liuxian Blvd, Nanshan District, 518055, Shenzhen, PR.China

Tel: +86 755 26835560/1/2

Fax: +86 755 26678789

Website: www.genrui-bio.com